IN THE CLAIMS:

1. (Currently Amended) A plasma display panel in which a plurality of pairs of first and second electrodes are disposed on a first substrate so as to be parallel to each other, a plurality of third electrodes are disposed on a second substrate, and main parts of a plurality of barrier ribs are disposed between adjacent third electrodes, the third electrodes being orthogonal to a longitudinal direction of display electrodes each of which consists of a pair of the first and second electrodes, wherein

a plurality of fourth electrodes are fixed to the barrier ribs in such a manner as to be inserted in the barrier ribs at a first distance from the first substrate, or areas of a surface of the first substrate facing the barrier ribs so as to be at least in vicinities of areas between adjacent display electrodes, the fourth electrodes being electrically exposed to discharge spaces which are defined by the barrier ribs.

2. - 3. (Canceled)

4. (Currently Amended) The plasma display panel of <u>Claim 1</u> Claim 2, further comprising:

a plurality of fifth electrodes which are inserted in the barrier ribs at a second distance from the first substrate.

2

5. (Original) The plasma display panel of Claim 4, wherein sub-parts of the barrier ribs, which bridge adjacent main parts of the barrier ribs, are substantially orthogonal to the third electrodes,

the fourth electrodes are fixed to the main parts of the barrier ribs, and the fifth electrodes are fixed to the sub-parts of the barrier ribs.

- 6. (Previously Presented) The plasma display panel of Claim 1, wherein sub-parts of the barrier ribs, which bridge adjacent main parts of the barrier ribs, are substantially orthogonal to the third electrodes.
- 7. (Currently Amended) A plasma display device in which a plurality of pairs of first and second electrodes are disposed on a first substrate so as to be parallel to each other, a plurality of third electrodes are disposed on a second substrate, and main parts of a plurality of barrier ribs are disposed between adjacent third electrodes, the third electrodes being orthogonal to a longitudinal direction of display electrodes each of which consists of a pair of the first and second electrodes, wherein

a plurality of fourth electrodes are <u>inserted in fixed to</u> the barrier ribs so as to be at least in vicinities of areas between adjacent display electrodes, the fourth electrodes being electrically exposed to discharge spaces which are defined by the barrier ribs, and

the plasma display device includes a driving circuit for applying a voltage to the fourth electrodes or for earthing the fourth electrodes.

- 8. (Original) The plasma display device of Claim 7, wherein the driving circuit applies a positive voltage to the fourth electrodes.
- 9. (Original) The plasma display device of Claim 8, wherein the fourth electrodes are at a first distance from the first substrate, and fixed to the barrier ribs in such a manner as to be inserted in the barrier ribs or disposed on surfaces of the barrier ribs.
 - 10. (Canceled)
- 11. (Currently Amended) The plasma display device of <u>Claim 9</u> <u>Claim 10</u>, wherein the driving circuit applies a first voltage pulse and a second voltage pulse to the first electrodes and the second electrodes respectively, and additionally applies a third voltage pulse to the fourth electrodes.
- 12. (Original) The plasma display device of Claim 11, further comprising:
 a plurality of fifth electrodes which are inserted in the barrier ribs at a second distance
 from the first substrate, wherein

the driving circuit applies a fourth voltage pulse to the fifth electrodes when outputting the first voltage pulse and the second voltage pulse at the same time.

4

13. (Original) The plasma display device of Claim 12, wherein sub-parts of the barrier ribs, which bridge adjacent main parts of the barrier ribs, are substantially orthogonal to the third electrodes,

the fourth electrodes are fixed to the main parts of the barrier ribs, and the fifth electrodes are fixed to the sub-parts of the barrier ribs.

14. (Previously Presented) The plasma display device of Claim 7, wherein sub-parts of the barrier ribs, which bridge adjacent main parts of the barrier ribs, are substantially orthogonal to the third electrodes.

15.- 16. (Canceled)

- 17. (Previously Presented) The plasma display panel of Claim 4, wherein sub-parts of the barrier ribs, which bridge adjacent main parts of the barrier ribs, are substantially orthogonal to the third electrodes.
- 18. (Previously Presented) The plasma display device of Claim 8, wherein sub-parts of the barrier ribs, which bridge adjacent main parts of the barrier ribs, are substantially orthogonal to the third electrodes.

- 19. (Previously Presented) The plasma display device of Claim 9, wherein sub-parts of the barrier ribs, which bridge adjacent main parts of the barrier ribs, are substantially orthogonal to the third electrodes.
 - 20. (Canceled)
- 21. (Previously Presented) The plasma display device of Claim 11, wherein sub-parts of the barrier ribs, which bridge adjacent main parts of the barrier ribs, are substantially orthogonal to the third electrodes.
- 22. (New) The plasma display device of Claim 1, wherein the plurality of fourth electrodes are at a first distance from the first substrate, and fixed to the barrier ribs in such a manner as to be inserted in the barrier ribs so as to form right angles with an address electrode.

6